

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA RENE PODWÓJNY

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	proponowana moc grzałki
600	236	4+4	60	100	550	6.5	4.0	194	323	405	-
600	294	5+5	60	100	550	8.0	5.0	242	404	506	-
600	352	6+6	60	100	550	9.5	6.0	291	485	607	-
600	410	7+7	60	100	550	11.5	7.0	339	565	708	-
600	468	8+8	60	100	550	13.0	8.5	388	646	810	-
600	526	9+9	60	100	550	14.5	9.5	436	727	911	-
600	584	10+10	60	100	550	16.0	10.5	484	807	1012	-
600	642	11+11	60	100	550	17.5	11.5	533	888	1113	-
1000	236	4+4	60	100	950	10.5	7.0	314	523	656	-
1000	294	5+5	60	100	950	13.0	8.5	392	654	820	-
1000	352	6+6	60	100	950	15.5	10.0	471	785	984	-
1000	410	7+7	60	100	950	18.0	12.0	550	916	1148	-
1000	468	8+8	60	100	950	20.5	13.5	628	1047	1312	-
1000	526	9+9	60	100	950	23.0	15.0	706	1177	1476	-
1000	584	10+10	60	100	950	26.0	17.0	785	1308	1640	-
1000	642	11+11	60	100	950	28.0	18.5	863	1439	1804	-
1500	236	4+4	60	100	1450	15.0	10.0	464	774	970	-
1500	294	5+5	60	100	1450	19.0	12.5	580	967	1212	-
1500	352	6+6	60	100	1450	23.0	15.0	697	1161	1455	-
1500	410	7+7	60	100	1450	26.5	17.5	812	1354	1697	-
1500	468	8+8	60	100	1450	31.0	20.0	928	1547	1940	-
1500	526	9+9	60	100	1450	34.0	22.5	1045	1741	2182	-
1500	584	10+10	60	100	1450	38.0	25.0	1160	1934	2424	-
1500	642	11+11	60	100	1450	41.5	27.5	1277	2128	2667	-
1800	236	4+4	60	100	1750	18.0	12.0	554	924	1158	-
1800	294	5+5	60	100	1750	22.5	15.0	693	1155	1448	-
1800	352	6+6	60	100	1750	27.0	18.0	832	1386	1737	-
1800	410	7+7	60	100	1750	31.5	21.0	970	1617	2027	-
1800	468	8+8	60	100	1750	36.0	24.0	1109	1848	2316	-
1800	526	9+9	60	100	1750	40.5	27.0	1247	2079	2606	-
1800	584	10+10	60	100	1750	45.1	30.0	1386	2310	2895	-
1800	642	11+11	60	100	1750	49.6	33.0	1525	2541	3185	-

Ze względu na nietypową budowę grzejnika nie ma możliwości podłączenia grzałki elektrycznej, zarówno w wersji pionowej jak i poziomej.