

**LENA**

wysokość	szerokość	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm <sup>3</sup> )	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	proponowana moc grzałki
500	430	45-55	60-70	400	3,5	1,5	81	135	168	300
500	530	45-55	60-70	500	4,0	2,0	107	178	223	300
500	630	45-55	60-70	600	4,5	2,5	135	225	280	300
750	430	45-55	60-70	400	5,0	2,5	144	240	299	300
750	530	45-55	60-70	500	6,0	3,0	172	287	357	400
750	630	45-55	60-70	600	7,0	3,0	203	339	424	400
950	430	45-55	60-70	400	6,5	3,5	200	334	416	400
950	530	45-55	60-70	500	7,5	3,5	251	418	520	600
950	630	45-55	60-70	600	8,5	4,0	272	454	568	600
1150	430	45-55	60-70	400	8,0	4,5	256	426	308	400
1150	530	45-55	60-70	500	9,5	4,5	294	490	613	600
1150	630	45-55	60-70	600	10,5	4,5	326	543	681	600
1350	430	45-55	60-70	400	9,5	5,0	264	440	550	400
1350	530	45-55	60-70	500	11,0	5,0	357	595	747	600
1350	630	45-55	60-70	600	12,5	6,0	382	637	799	600
1550	430	45-55	60-70	400	11,0	6,0	339	565	706	600
1550	530	45-55	60-70	500	13,0	7,0	382	636	795	600
1550	630	45-55	60-70	600	15,0	7,5	413	688	863	800