

KOMEX

STYLowe CIEPŁO

DANE TECHNICZNE GRZEJNIKA ALEX

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20° C	moc [W] 75/65/20° C	moc [W] 90/70/20° C	proponowana moc grzałki
600	310	8	40	100	500	8,0	4,0	194	323	405	300
600	390	10	40	100	500	10,0	5,0	242	404	506	300
600	470	12	40	100	500	12,0	6,0	291	485	608	300
600	550	14	40	100	500	14,0	7,0	340	566	709	600
600	630	16	40	100	500	16,0	8,0	388	647	811	600
1100	310	8	40	100	1000	14,0	7,0	340	567	711	600
1100	390	10	40	100	1000	17,5	8,5	425	709	889	600
1100	470	12	40	100	1000	21,0	10,5	511	851	1067	800
1100	550	14	40	100	1000	25,0	12,0	596	993	1245	800
1100	630	16	40	100	1000	28,0	13,5	681	1135	1423	1000
1500	310	8	40	100	1400	19,0	9,0	458	763	956	600
1500	390	10	40	100	1400	23,5	11,5	572	954	1195	800
1500	470	12	40	100	1400	28,0	14,0	687	1145	1435	1000
1500	550	14	40	100	1400	33,0	16,0	801	1335	1674	1000
1500	630	16	40	100	1400	37,5	18,5	916	1526	1913	-
1800	310	8	40	100	1700	22,5	11,0	545	909	1140	800
1800	390	10	40	100	1700	28,0	13,5	682	1137	1425	1000
1800	470	12	40	100	1700	34,0	16,5	818	1364	1710	-
1800	550	14	40	100	1700	40,0	19,0	955	1592	1995	-
1800	630	16	40	100	1700	45,0	22,0	1092	1820	2281	-
2000	310	8	40	100	1900	25,0	12,0	604	1007	1262	1000
2000	390	10	40	100	1900	31,0	15,0	755	1259	1578	-
2000	470	12	40	100	1900	37,2	18,0	907	1511	1894	-
2000	550	14	40	100	1900	43,5	24,0	1058	1763	2210	-
2000	630	16	40	100	1900	50,0	24,0	1209	2015	2526	-