

IRMA

wysokość	szerokość	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20 °C	moc [W] 75/65/20 °C	moc [W] 90/70/20 °C	proponowana moc grzałki
500	430	45-55	93-103	400	3,5	2,0	90	150	187	300
500	530	45-55	93-103	500	4,0	2,0	116	193	240	300
500	630	45-55	93-103	600	4,5	2,5	144	240	300	300
750	430	45-55	93-103	400	5,0	3,0	162	270	336	400
750	530	45-55	93-103	500	6,0	3,0	190	317	395	400
750	630	45-55	93-103	600	6,5	3,5	212	354	444	600
950	430	45-55	93-103	400	6,5	4,0	209	349	435	300
950	530	45-55	93-103	500	7,5	4,5	269	448	560	300
950	630	45-55	93-103	600	8,5	4,5	350	584	733	400
1150	430	45-55	93-103	400	8,0	5,0	283	471	586	600
1150	530	45-55	93-103	500	9,5	5,5	321	535	669	600
1150	630	45-55	93-103	600	10,5	5,0	353	588	735	800
1350	430	45-55	93-103	400	9,5	6,0	297	495	616	300
1350	530	45-55	93-103	500	11,0	6,5	384	640	800	300
1350	630	45-55	93-103	600	13,0	6,0	409	682	853	600
1550	430	45-55	93-103	400	11,5	6,0	375	625	781	600
1550	530	45-55	93-103	500	13,5	7,0	418	696	873	800
1550	630	45-55	93-103	600	13,0	7,5	449	748	939	800