

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA IRMA

wysokość	szerokość	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
500	430	45-55	93-103	400	3,5	1,5	103	191	238	300
500	530	45-55	93-103	500	4,0	1,5	127	236	294	300
500	630	45-55	93-103	600	4,5	2,0	151	280	349	300
750	430	45-55	93-103	400	5,0	2,5	159	295	368	300
750	530	45-55	93-103	500	6,0	2,5	196	364	454	400
750	630	45-55	93-103	600	6,5	3,0	233	433	540	600
950	430	45-55	93-103	400	6,5	3,0	205	382	477	400
950	530	45-55	93-103	500	7,5	3,5	253	471	588	400
950	630	45-55	93-103	600	8,5	3,5	300	559	698	600
1150	430	45-55	93-103	400	8,0	3,5	248	462	577	600
1150	530	45-55	93-103	500	9,5	4,0	306	570	712	600
1150	630	45-55	93-103	600	10,5	4,5	363	677	845	800
1350	430	45-55	93-103	400	9,5	4,0	295	550	687	600
1350	530	45-55	93-103	500	11,0	4,5	364	678	846	800
1350	630	45-55	93-103	600	13,0	5,0	433	806	1006	800
1550	430	45-55	93-103	400	11,5	4,5	339	633	791	600
1550	530	45-55	93-103	500	13,5	5,0	418	780	974	800
1550	630	45-55	93-103	600	13,0	6,0	497	927	1158	800