

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA RENE POJEDYŃCZY Z OSŁONĄ SZKLANĄ

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
600	352	6	52	110	550	5.5	3.5	135	259	325	300
600	410	7	52	110	550	6.0	4.0	157	302	379	300
600	468	8	52	110	550	7.0	4.5	180	345	433	300
600	526	9	52	110	550	7.5	5.0	202	389	487	300
600	584	10	52	110	550	8.5	5.5	225	432	541	600
600	642	11	52	110	550	9.5	6.0	243	475	595	600
1000	352	6	52	110	950	8.0	5.5	211	409	513	300
1000	410	7	52	110	950	9.5	6.0	245	478	599	300
1000	468	8	52	110	950	11.0	7.0	279	546	684	600
1000	526	9	52	110	950	12.0	8.0	314	614	770	600
1000	584	10	52	110	950	13.5	9.0	349	682	855	600
1000	642	11	52	110	950	15.0	9.5	379	750	940	800
1500	352	6	52	110	1450	12.0	8.0	304	597	749	600
1500	410	7	52	110	1450	13.5	9.0	354	697	873	600
1500	468	8	52	110	1450	15.5	10.0	398	796	998	800
1500	526	9	52	110	1450	17.5	11.5	448	896	1123	800
1500	584	10	52	110	1450	19.5	13.0	498	995	1247	1000
1500	642	11	52	110	1450	21.5	14.0	548	1095	1372	1000
1800	352	6	52	110	1750	14.0	9.0	355	710	890	600
1800	410	7	52	110	1750	16.0	10.5	414	828	1038	800
1800	468	8	52	110	1750	18.5	12.0	472	946	1186	1000
1800	526	9	52	110	1750	21.0	13.5	531	1065	1335	1000
1800	584	10	52	110	1750	23.0	15.0	590	1183	1483	1000
1800	642	11	52	110	1750	25.5	16.5	649	1301	1631	1000