

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA VICTORIA PODWÓJNA Z OSŁONĄ DEKORACYJNĄ

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
600	295	4+4	43	69	550	8,1	2,5	241	401	503	-
600	445	6+6	43	69	550	12,0	3,0	380	634	795	-
600	595	8+8	43	69	550	16,0	4,0	494	823	1032	-
600	745	10+10	43	69	550	19,0	5,5	605	1009	1264	-
600	895	12+12	43	69	550	22,9	6,5	715	1191	1493	-
600	1045	14+14	43	69	550	27,0	7,5	821	1369	1716	-
1000	295	4+4	43	69	950	13,0	3,5	373	622	779	-
1000	445	6+6	43	69	950	19,0	5,0	586	977	1225	-
1000	595	8+8	43	69	950	25,6	6,5	761	1269	1590	-
1000	745	10+10	43	69	950	32,0	8,0	923	1538	1928	-
1000	895	12+12	43	69	950	38,0	10,0	1092	1820	2281	-
1000	1045	14+14	43	69	950	44,4	12,0	1264	2106	2639	-
1500	295	4+4	43	69	1450	19,0	5,0	532	887	1112	-
1500	445	6+6	43	69	1450	28,5	7,0	844	1406	1762	-
1500	595	8+8	43	69	1450	37,7	9,5	1076	1794	2248	-
1500	745	10+10	43	69	1450	47,0	12,0	1326	2210	2769	-
1500	895	12+12	43	69	1450	52,0	13,0	1560	2600	3258	-
1500	1045	14+14	43	69	1450	56,5	14,5	1802	3003	3763	-
1800	295	4+4	43	69	1750	22,6	6,0	625	1042	1306	-
1800	445	6+6	43	69	1750	33,7	8,5	980	1633	2047	-
1800	595	8+8	43	69	1750	45,0	11,5	1270	2116	2652	-
1800	745	10+10	43	69	1750	56,2	14,0	1551	2585	3240	-
1800	895	12+12	43	69	1750	67,4	15,5	1840	3067	3843	-
1800	1045	14+14	43	69	1750	78,3	17,0	2078	3464	4341	-
2000	295	4+4	43	69	1950	25,0	6,5	686	1144	1434	-
2000	445	6+6	43	69	1950	37,4	9,5	1052	1753	2197	-
2000	595	8+8	43	69	1950	49,9	12,5	1376	2294	2875	-

2000	745	10+10	43	69	1950	62,5	16,0	1692	2820	3534	-
2000	895	12+12	43	69	1950	75,0	17,5	1978	3296	4130	-
2000	1045	14+14	43	69	1950	87,0	19,0	2306	3844	4817	-