

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA VICTORIA POJEDYŃCZA Z WKŁADKĄ ZAWOROWĄ

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
300	600	4	49	72	50	4,8	1,5	162	270	338	-
450	600	6	49	72	50	6,8	2,0	242	404	507	-
600	600	8	49	72	50	8,8	2,5	315	525	658	-
300	900	4	49	72	50	5,5	2,0	202	337	422	-
450	900	6	49	72	50	8,0	2,5	303	505	633	-
600	900	8	49	72	50	11,5	3,0	394	656	822	-
300	1000	4	49	72	50	7,0	2,0	245	409	512	-
450	1000	6	49	72	50	10,2	3,0	368	614	769	-
600	1000	8	49	72	50	14,0	3,5	478	796	999	-
300	1200	4	49	72	50	8,0	2,5	294	490	614	-
450	1200	6	49	72	50	13,0	3,5	442	736	922	-
600	1200	8	49	72	50	15,5	4,0	573	955	1198	-
300	1500	4	49	72	50	9,9	3,0	346	577	724	-
450	1500	6	49	72	50	16,1	3,5	519	865	1085	-
600	1500	8	49	72	50	21,3	5,0	674	1124	1411	-
300	1800	4	49	72	50	11,6	3,0	406	676	847	-
450	1800	6	49	72	50	19,0	4,0	608	1013	1270	-
600	1800	8	49	72	50	25,1	5,5	790	1316	1651	-
300	2000	4	49	72	50	12,8	3,5	444	740	928	-
450	2000	6	49	72	50	21,0	4,5	666	1110	1392	-
600	2000	8	49	72	50	27,8	6,0	866	1443	1808	-