

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA RENE PODWÓJNY Z OSŁONĄ SZKLANĄ

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
600	352	6+6	61	120	550	13,6	6,0	291	485	607	-
600	410	7+7	61	120	550	16,5	7,0	339	565	708	-
600	468	8+8	61	120	550	18,6	8.5	388	646	810	-
600	526	9+9	61	120	550	20,8	9.5	436	727	911	-
600	584	10+10	61	120	550	23,0	10.5	484	807	1012	-
600	642	11+11	61	120	550	25,2	11.5	533	888	1113	-
1000	352	6+6	61	120	950	22,0	10,0	471	785	984	-
1000	410	7+7	61	120	950	25,7	12,0	550	916	1148	-
1000	468	8+8	61	120	950	26,0	13.5	628	1047	1312	-
1000	526	9+9	61	120	950	29,5	15.0	706	1177	1476	-
1000	584	10+10	61	120	950	33,5	17.0	785	1308	1640	-
1000	642	11+11	61	120	950	38,0	18,5	863	1439	1804	-
1500	352	6+6	61	120	1450	33,0	15,0	697	1161	1455	-
1500	410	7+7	61	120	1450	38,0	17,5	812	1354	1697	-
1500	468	8+8	61	120	1450	38,5	20,0	928	1547	1940	-
1500	526	9+9	61	120	1450	45,0	22.5	1045	1741	2182	-
1500	584	10+10	61	120	1450	50,0	25,0	1160	1934	2424	-
1500	642	11+11	61	120	1450	55,5	27.5	1277	2128	2667	-
1800	352	6+6	61	120	1750	38,5	18,0	832	1386	1737	-
1800	410	7+7	61	120	1750	45,0	21,0	970	1617	2027	-
1800	468	8+8	61	120	1750	53,0	24.0	1109	1848	2316	-
1800	526	9+9	61	120	1750	59,5	27.0	1247	2079	2606	-
1800	584	10+10	61	120	1750	66,1	30.0	1386	2310	2895	-
1800	642	11+11	61	120	1750	72,6	33.0	1525	2541	3185	-