

KOMEX

STYLowe CIEPŁO

DANE TECHNICZNE GRZEJNIKA ELENA POJEDYNCZA

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
1000	300	10	60	105	950	9,7	3,5	262	436	546	-
1000	390	13	60	105	950	12,6	4,5	340	567	710	-
1000	450	15	60	105	950	14,4	5,0	392	654	820	-
1000	540	18	60	105	950	17,4	6,0	471	785	984	-
1000	600	20	60	105	950	19,4	6,5	523	872	1093	-
1500	300	10	60	105	1450	14,2	5,0	384	640	802	-
1500	390	13	60	105	1450	18,4	6,5	499	831	1042	-
1500	450	15	60	105	1450	21,2	7,5	575	959	1203	-
1500	540	18	60	105	1450	25,5	8,5	691	1151	1443	-
1500	600	20	60	105	1450	28,3	9,5	767	1279	1603	-
1800	300	10	60	105	1750	16,9	6,0	457	762	955	-
1800	390	13	60	105	1750	21,9	7,5	594	990	1241	-
1800	450	15	60	105	1750	25,3	8,5	686	1143	1432	-
1800	540	18	60	105	1750	30,3	10,5	823	1371	1719	-
1800	600	20	60	105	1750	33,7	11,5	914	1523	1910	-
2000	300	10	60	105	1950	18,7	6,5	506	843	1057	-
2000	390	13	60	105	1950	24,3	8,0	658	1096	1374	-
2000	450	15	60	105	1950	28,0	9,5	759	1265	1585	-
2000	540	18	60	105	1950	33,6	11,5	911	1518	1902	-
2000	600	20	60	105	1950	37,3	12,5	1012	1686	2114	-