

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA GINA INVEST

wysokość	szerokość	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
480	450	50-60	160-170	400	3,8	2,0	82	155	194	300
480	550	50-60	160-170	500	4,2	2,5	102	192	241	300
720	450	50-60	160-170	400	5,5	3,0	142	267	335	300
720	550	50-60	160-170	500	6,2	3,5	176	333	418	300
940	450	50-60	160-170	400	7,2	4,0	197	372	467	400
940	550	50-60	160-170	500	8,1	5,0	245	462	579	600
1120	450	50-60	160-170	400	8,8	5,0	258	487	611	600
1120	550	50-60	160-170	500	9,8	6,0	321	604	756	800
1350	450	50-60	160-170	400	10,5	6,0	348	655	821	800
1350	550	50-60	160-170	500	11,8	7,0	432	813	1018	1000
1580	450	50-60	160-170	400	12,5	7,0	483	907	1135	1000
1580	550	50-60	160-170	500	14,0	8,5	602	1130	1414	1000