

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA VICTORIA POJEDYNCZA Z OSŁONĄ SZKLANĄ

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
600	445	6	49	92	550	11,8	2,0	211	352	441	300
600	595	8	49	92	550	15,3	2,5	274	457	573	300
600	745	10	49	92	550	19,4	3,0	336	560	702	400
600	895	12	49	92	550	23,4	4,0	397	661	828	600
600	1045	14	49	92	550	27,0	4,5	456	760	953	600
1000	445	6	49	92	950	18,7	3,0	320	534	669	300
1000	595	8	49	92	950	24,9	3,5	416	693	869	400
1000	745	10	49	92	950	31,1	4,5	509	849	1065	600
1000	895	12	49	92	950	37,3	5,5	602	1003	1257	800
1000	1045	14	49	92	950	43,6	7,0	692	1154	1446	1000
1500	445	6	49	92	1450	29,6	3,5	452	753	944	400
1500	595	8	49	92	1450	38,8	5,0	587	978	1227	800
1500	745	10	49	92	1450	48,9	6,0	719	1198	1503	800
1500	895	12	49	92	1450	58,0	7,0	848	1414	1774	-
1500	1045	14	49	92	1450	68,2	8,0	976	1627	2040	-
1800	445	6	49	92	1750	34,5	4,0	529	881	1105	600
1800	520	7	49	92	1750	41,0	4,5	616	1027	1289	800
1800	595	8	49	92	1750	46,6	5,5	687	1145	1436	1000
1800	745	10	49	92	1750	57,8	6,8	842	1403	1759	-
1800	895	12	49	92	1750	69,9	8,2	993	1655	2076	-
1800	1045	14	49	92	1750	81,2	9,5	1143	1905	2388	-
2000	445	6	49	92	1950	38,5	4,5	580	966	1211	800
2000	595	8	49	92	1950	51,3	6,1	753	1255	1573	1000
2000	745	10	49	92	1950	64,2	7,5	922	1537	1927	-
2000	895	12	49	92	1950	86,0	9,1	1088	1814	2275	-
2000	1045	14	49	92	1950,0	96,4	10	1252	2087	2617	-