

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA RENE PODWÓJNY

wysokość	szerokość	liczba elementów	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm3)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
600	236	4+4	61	100	550	6.5	4.0	194	323	405	-
600	294	5+5	61	100	550	8.0	5.0	242	404	506	-
600	352	6+6	61	100	550	9.5	6.0	291	485	607	-
600	410	7+7	61	100	550	11.5	7.0	339	565	708	-
600	468	8+8	61	100	550	13.0	8.5	388	646	810	-
600	526	9+9	61	100	550	14.5	9.5	436	727	911	-
600	584	10+10	61	100	550	16.0	10.5	484	807	1012	-
600	642	11+11	61	100	550	17.5	11.5	533	888	1113	-
1000	236	4+4	61	100	950	10.5	7.0	314	523	656	-
1000	294	5+5	61	100	950	13.0	8.5	392	654	820	-
1000	352	6+6	61	100	950	15.5	10.0	471	785	984	-
1000	410	7+7	61	100	950	18.0	12.0	550	916	1148	-
1000	468	8+8	61	100	950	20.5	13.5	628	1047	1312	-
1000	526	9+9	61	100	950	23.0	15.0	706	1177	1476	-
1000	584	10+10	61	100	950	26.0	17.0	785	1308	1640	-
1000	642	11+11	61	100	950	28.0	18,5	863	1439	1804	-
1500	236	4+4	61	100	1450	15.0	10.0	464	774	970	-
1500	294	5+5	61	100	1450	19.0	12.5	580	967	1212	-
1500	352	6+6	61	100	1450	23.0	15.0	697	1161	1455	-
1500	410	7+7	61	100	1450	26.5	17.5	812	1354	1697	-
1500	468	8+8	61	100	1450	31.0	20,0	928	1547	1940	-
1500	526	9+9	61	100	1450	34.0	22.5	1045	1741	2182	-
1500	584	10+10	61	100	1450	38.0	25,0	1160	1934	2424	-
1500	642	11+11	61	100	1450	41.5	27.5	1277	2128	2667	-
1800	236	4+4	61	100	1750	18.0	12.0	554	924	1158	-
1800	294	5+5	61	100	1750	22.5	15.0	693	1155	1448	-
1800	352	6+6	61	100	1750	27.0	18.0	832	1386	1737	-

1800	410	7+7	61	100	1750	31.5	21.0	970	1617	2027	–
1800	468	8+8	61	100	1750	36.0	24.0	1109	1848	2316	–
1800	526	9+9	61	100	1750	40.5	27.0	1247	2079	2606	–
1800	584	10+10	61	100	1750	45.1	30.0	1386	2310	2895	–
1800	642	11+11	61	100	1750	49.6	33.0	1525	2541	3185	–
2000	236	4+4	61	100	1950	20.0	13.5	616	1027	1287	–
2000	294	5+5	61	100	1950	25.0	16.5	770	1283	1609	–
2000	352	6+6	61	100	1950	30.0	20.0	924	1540	1930	–
2000	410	7+7	61	100	1950	35.0	23.5	1078	1797	2252	–
2000	468	8+8	61	100	1950	40.0	26.5	1232	2053	2573	–
2000	526	9+9	61	100	1950	45.0	30.0	1386	2310	2896	–
2000	584	10+10	61	100	1950	50.1	33.5	1540	2567	3217	–
2000	642	11+11	61	100	1950	55.1	36.5	1694	2823	3539	–