

KOMEX

STYLOWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA REGINA

wysokość	szerokość	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20°C	moc [W] 75/65/20°C	moc [W] 90/70/20°C	proponowana moc grzałki
720	300	50-60	155-165	250	7,4	2,5	192	354	441	300
720	400	50-60	155-165	350	8,0	3,0	245	454	566	400
720	450	50-60	155-165	400	8,5	3,5	269	499	622	400
720	500	50-60	155-165	450	9,0	4,0	299	554	691	400
720	550	50-60	155-165	500	9,4	4,0	328	609	759	400
940	300	50-60	155-165	250	9,0	3,5	245	454	565	400
940	400	50-60	155-165	350	9,5	4,0	308	582	725	600
940	450	50-60	155-165	400	10,0	4,5	348	646	805	600
940	500	50-60	155-165	450	11,4	5,0	383	710	885	800
940	550	50-60	155-165	500	12,0	6,0	421	781	974	600
1120	450	50-60	155-165	400	13,2	6,5	410	761	949	800
1120	550	50-60	155-165	500	14,6	7,0	502	930	1159	800
1350	450	50-60	155-165	400	17,0	9,0	494	917	1143	1000
1350	550	50-60	155-165	500	18,5	9,5	604	1121	1397	1000
1580	400	50-60	155-165	350	18,0	10,5	521	966	1204	1000
1580	450	50-60	155-165	400	18,7	11,0	579	1073	1338	1000
1580	500	50-60	155-165	450	19,0	11,5	636	1180	1471	1000
1580	550	50-60	155-165	500	20,5	12,0	700	1298	1618	1000