

KOMEX

STYLÓWE CIEPŁO

DANE TECHNICZNE GRZEJNIKA MAX

wysokość	szerokość	głębokość od ściany do środka osi przyłączy	głębokość całkowita od ściany	rozstaw otworów montażowych	ciężar (kg)	pojemność (dm ³)	moc [W] 55/45/20 °C	moc [W] 75/65/20 °C	moc [W] 90/70/20 °C	proponowana moc grzałki
1000	330/7	45	65	970	9,5	5,5	194	267	320	-
1000	465/10	45	65	970	13,7	7,5	279	380	456	-
1000	600/13	45	65	970	18,1	9,5	372	507	608	-
1200	330/7	45	65	1170	11,4	7,0	251	342	410	-
1200	465/10	45	65	1170	16,4	9,5	366	499	599	-
1200	600/13	45	65	1170	21,7	12,5	488	666	799	-
1400	330/7	45	65	1370	13,3	8,0	297	405	486	-
1400	465/10	45	65	1370	19,1	11,0	443	604	725	-
1400	600/13	45	65	1370	25,3	14,0	592	807	968	-
1600	330/7	45	65	1570	15,2	9,0	343	468	562	-
1600	465/10	45	65	1570	21,9	12,5	507	692	830	-
1600	600/13	45	65	1570	29,0	16,0	678	924	1109	-
1800	330/7	45	65	1770	17,1	10,0	414	564	677	-
1800	465/10	45	65	1770	24,6	14,0	620	846	1015	-
1800	600/13	45	65	1770	32,6	18,0	827	1128	1354	-